

5 **ACTIVE ALT TAG IN HTML DOCUMENTS TO INCREASE THE
ACCESSIBILITY TO USERS WITH VISUAL, AUDIO IMPAIRMENT**

BACKGROUND OF THE INVENTION

1. Technical Field:

10 The present invention relates to computer network environments. More specifically, the present invention relates to accessing electronic documents.

2. Description of Related Art:

15 Information on the World Wide Web is typically made available by structuring the information into a visual presentation. Hypertext Markup Language (HTML) is used by the web author to define the visual structure. The end user is presented with this information by viewing 20 the information on a computer display, after the information has been rendered into a visual format by a web browser (e.g. Netscape Navigator or Microsoft Internet Explorer).

25 Web pages are often created with various multimedia resources such as Video Clip, Audio, and Images. The web designer normally selects a primary format which will make the maximum impact on a normal user. Sometimes these multimedia formats may not be appropriate for users with various visual or hearing impairments.

30 Currently, well designed web pages use the HTML ALT tags to specify alternate resource formats for a multimedia resource. For example, a video clip may be

specified as a primary format. The clip's text equivalent or audio version may be specified as the alternate format. Users, using the browser settings, may turn off the primary format and instead access the
5 alternate format. However, the setting in a browser must be applied to the whole page, until the browser setting is changed.

Therefore, a more flexible approach for selecting alternate web page formats would be desirable.

SUMMARY OF THE INVENTION

The present invention provides a method, program and system for providing access to alternate formats within an electronic document. The invention comprises parsing a web page and creating a document object model (DOM), and then parsing the alternate format attribute of an image element within the DOM. A browser then displays the web page containing an image (or images) according to the default settings of the browser. A user interface is specified which allows the user to select alternate formats for the default image. This user interface may be in the form of a pop up menu that is presented to the user in response to an input command, such as a right mouse click on the default image. The user can then select an alternate format which replaces the original image in the web page. Alternate formats may include text, audio, or tactile formats.

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the invention are set forth in the appended claims. The 5 invention itself, however, as well as a preferred mode of use, further objectives and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with the accompanying drawings, wherein:

10 **Figure 1** depicts a pictorial representation of a network of data processing systems in which the present invention may be implemented;

15 **Figure 2** depicts a block diagram of a data processing system that may be implemented as a server in accordance with a preferred embodiment of the present invention;

Figure 3 depicts a block diagram illustrating a data processing system in which the present invention may be implemented;

20 **Figure 4** depicts a block diagram of a browser program in accordance with a preferred embodiment of the present invention;

Figure 5 depicts a block diagram illustrating a Document Object Model in accordance with the prior art;

25 **Figure 6** depicts a flowchart illustrating the processing of an HTML document in accordance with the prior art;

Figure 7 depicts a flowchart illustrating the use of active ALT tags in accordance with the present invention; and

30 **Figure 8** depicts a pictorial diagram illustrating ALT menu on a web page in accordance with the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

5 With reference now to the figures, **Figure 1** depicts a pictorial representation of a network of data processing systems in which the present invention may be implemented. Network data processing system **100** is a network of computers in which the present invention may be
10 implemented. Network data processing system **100** contains a network **102**, which is the medium used to provide communications links between various devices and computers connected together within network data processing system **100**. Network **102** may include connections, such as wire,
15 wireless communication links, or fiber optic cables.

 In the depicted example, a server **104** is connected to network **102** along with storage unit **106**. In addition, clients **108**, **110**, and **112** also are connected to network **102**. These clients **108**, **110**, and **112** may be, for example, personal computers or network computers. In the depicted example, server **104** provides data, such as boot files, operating system images, and applications to clients **108-112**. Clients **108**, **110**, and **112** are clients to server **104**. Network data processing system **100** may include
20 additional servers, clients, and other devices not shown.

 In the depicted example, network data processing system **100** is the Internet with network **102** representing a worldwide collection of networks and gateways that use the TCP/IP suite of protocols to communicate with one another.
30 At the heart of the Internet is a backbone of high-speed data communication lines between major nodes or host computers, consisting of thousands of commercial,

government, educational and other computer systems that route data and messages. Of course, network data processing system 100 also may be implemented as a number of different types of networks, such as for example, an 5 intranet, a local area network (LAN), or a wide area network (WAN). **Figure 1** is intended as an example, and not as an architectural limitation for the present invention.

Referring to **Figure 2**, a block diagram of a data processing system that may be implemented as a server, 10 such as server 104 in **Figure 1**, is depicted in accordance with a preferred embodiment of the present invention.

Data processing system 200 may be a symmetric multiprocessor (SMP) system including a plurality of processors 202 and 204 connected to system bus 206.

15 Alternatively, a single processor system may be employed. Also connected to system bus 206 is memory controller/cache 208, which provides an interface to local memory 209. I/O bus bridge 210 is connected to system bus 206 and provides an interface to I/O bus 212. Memory 20 controller/cache 208 and I/O bus bridge 210 may be 20 integrated as depicted.

Peripheral component interconnect (PCI) bus bridge 214 connected to I/O bus 212 provides an interface to PCI local bus 216. A number of modems may be connected to PCI 25 bus 216. Typical PCI bus implementations will support four PCI expansion slots or add-in connectors.

Communications links to network computers 108-112 in **Figure 1** may be provided through modem 218 and network adapter 220 connected to PCI local bus 216 through add-in 30 boards.

Additional PCI bus bridges 222 and 224 provide interfaces for additional PCI buses 226 and 228, from

which additional modems or network adapters may be supported. In this manner, data processing system 200 allows connections to multiple network computers. A memory-mapped graphics adapter 230 and hard disk 232 may 5 also be connected to I/O bus 212 as depicted, either directly or indirectly.

Those of ordinary skill in the art will appreciate that the hardware depicted in **Figure 2** may vary. For example, other peripheral devices, such as optical disk 10 drives and the like, also may be used in addition to or in place of the hardware depicted. The depicted example is not meant to imply architectural limitations with respect to the present invention.

The data processing system depicted in **Figure 2** may 15 be, for example, an IBM RISC/System 6000 system, a product of International Business Machines Corporation in Armonk, New York, running the Advanced Interactive Executive (AIX) operating system.

With reference now to **Figure 3**, a block diagram 20 illustrating a data processing system is depicted in which the present invention may be implemented. Data processing system 300 is an example of a client computer. Data processing system 300 employs a peripheral component interconnect (PCI) local bus architecture. Although the 25 depicted example employs a PCI bus, other bus architectures such as Accelerated Graphics Port (AGP) and Industry Standard Architecture (ISA) may be used.

Processor 302 and main memory 304 are connected to PCI local bus 306 through PCI bridge 308. PCI bridge 308 also 30 may include an integrated memory controller and cache memory for processor 302. Additional connections to PCI local bus 306 may be made through direct component

interconnection or through add-in boards. In the depicted example, local area network (LAN) adapter **310**, SCSI host bus adapter **312**, and expansion bus interface **314** are connected to PCI local bus **306** by direct component connection. In contrast, audio adapter **316**, graphics adapter **318**, and audio/video adapter **319** are connected to PCI local bus **306** by add-in boards inserted into expansion slots. Expansion bus interface **314** provides a connection for a keyboard and mouse adapter **320**, modem **322**, and additional memory **324**. Small computer system interface (SCSI) host bus adapter **312** provides a connection for hard disk drive **326**, tape drive **328**, CD-ROM drive **330**, and DVD drive **332**. Typical PCI local bus implementations will support three or four PCI expansion slots or add-in connectors.

An operating system runs on processor **302** and is used to coordinate and provide control of various components within data processing system **300** in **Figure 3**. The operating system may be a commercially available operating system, such as Windows 2000, which is available from Microsoft Corporation. An object oriented programming system such as Java may run in conjunction with the operating system and provide calls to the operating system from Java programs or applications executing on data processing system **300**. "Java" is a trademark of Sun Microsystems, Inc. Instructions for the operating system, the object-oriented operating system, and applications or programs are located on storage devices, such as hard disk drive **326**, and may be loaded into main memory **304** for execution by processor **302**.

Those of ordinary skill in the art will appreciate

that the hardware in **Figure 3** may vary depending on the implementation. Other internal hardware or peripheral devices, such as flash ROM (or equivalent nonvolatile memory) or optical disk drives and the like, may be used 5 in addition to or in place of the hardware depicted in **Figure 3**. Also, the processes of the present invention may be applied to a multiprocessor data processing system.

As another example, data processing system 300 may 10 be a stand-alone system configured to be bootable without relying on some type of network communication interface, whether or not data processing system 300 comprises some type of network communication interface. As a further example, data processing system 300 may be a Personal 15 Digital Assistant (PDA) device, which is configured with ROM and/or flash ROM in order to provide non-volatile memory for storing operating system files and/or user-generated data.

The depicted example in **Figure 3** and above-described 20 examples are not meant to imply architectural limitations. For example, data processing system 300 also may be a notebook computer or hand held computer in addition to taking the form of a PDA. Data processing system 300 also may be a kiosk or a Web appliance.

25 Turning next to **Figure 4**, a block diagram of a browser program is depicted in accordance with a preferred embodiment of the present invention. Browser 400 includes a user interface 402, which is a graphical user interface (GUI) that allows the user to interface or 30 communicate with browser 400. This interface provides for selection of various functions through menus 404 and allows for navigation through the navigation button 406

or selections. For example, menu **404** may allow a user to perform various functions, such as saving a file, opening a new window, displaying a history, and entering a URL.

Navigation **406** allows for a user to navigate various

5 pages and to select web sites for viewing. For example, navigation **406** may allow a user to see a previous page or a subsequent page relative to the present page.

Preferences may be set through preferences **408**.

Communications **410** is the mechanism with which browser **400** receives documents and other resources from a network such as the Internet. Further, communications **410** is used to send or upload documents and resources onto a network. In the depicted example, communication **410** uses HTTP. However, other protocols are possible.

15 Documents that are received by browser **400** are processed by language interpretation **412**, which includes an HTML unit **414**. Language interpretation **412** will process a document for presentation on graphical display **416**. In particular, HTML statements are processed by HTML unit

20 **414** for presentation.

Graphical display **416** includes layout unit **418**, rendering unit **420**, and window management **422**. These units are involved in presenting web pages to a user based on results from language interpretation **412**.

25 Browser **400** is presented as an example of a browser program in which the present invention may be embodied.

Browser **400** is not meant to imply architectural limitations to the present invention. Presently available browsers may include additional functions not shown or may omit functions shown in browser **400**. As used herein, the term "browser" encompasses any software

application used to view or navigate for information or data (e.g., something that assist a user to browser) in a distributed data base where the distributed database is typically the Internet or World Wide Web.

5 Referring to **Figure 5**, a block diagram illustrating a Document Object Model is depicted in accordance with the prior art. HTML, which is used to provide a visual structure to a web page, also provides a semantic structure to the page. Well known techniques exist for 10 parsing an HTML source file into a parse tree, in which the various structural elements and relationships among the elements are apparent from the topology of the parse tree. The parse tree is also called a Document Object Model (DOM). The document represented by DOM 500 has 15 been parsed into its main components: HTML Document Element 501, HTML Title element 502, and HTML Image element 503. The HTML document element 501 is the root of the HTML document represented by DOM 500. In addition, **Figure 5** depicts the attributes of image 20 element 503. These attributes include source (SRC) 504 and alternative (ALT) 505.

The DOM is a standard developed at the World Wide Web consortium for a platform- and language-independent interface to the structure and content of HTML and 25 Extensible Markup Language (XML) documents. DOM uses Object Management Groups Interface Definition Language (IDL-ISO 14750) to express its object types. In DOM, an HTML or XML document is represented as a hierarchical collection of Node objects. Nodes are joined together in 30 parent/child relationships. The HTML components of DOM add functionality and convenience functions for HTML scripting applications.

Referring to **Figure 6**, a flowchart illustrating the processing of an HTML document is depicted in accordance with the prior art. When an HTML file is loaded, the browser parses the document source file and creates an input DOM structure in memory (step **601**). The browser formats the DOM structure by determining the output medium and assigning the appropriate attributes to the DOM elements (step **602**). The browser then populates the DOM with the elements (step **603**) and renders the document objects in the requested medium (step **604**).

The present invention provides an "ACTIVE" ALT tag for a multimedia resource that gives the user the ability to choose an appropriate format from a list of alternate formats. The list can be a pop up menu, an audio list, or a tactile menu. The tag can be activated by right clicking or double clicking on a mouse, or by any other means by which options and menus are usually accessed.

Referring to **Figure 7**, a flowchart illustrating the use of active ALT tags is depicted in accordance with the present invention. Using the DOM from **Figure 5**, the browser is configured to parse the ALT attribute **505** of the HTML image element **503** (step **701**). A user interface is specified using XML-based User Interface Language (XUL) (step **702**). Open source browser windows are often designed in XUL, which uses HTML/Cascading Style Sheets (CSS) and the DOM. Commands and actions for the windows are handled mostly with Javascript. Because the user interface is configurable through markup, it is not hard coded in the source. Instead it is loaded at runtime, enabling programmers to tweak the interface without having to recompile the source code. An example of a XUL script to add a pull down menu is as follows:

```
5      <window>
       <menubar>
         <menu name= "formats">
           <MenuItem name= "depth map" onclick=
             "displaydepthmap()"/>
             <MenuItem name= "intensity map" onclick=
               "displayintensitymap()"/>
           </menu>
10    </menubar>
       </window>
```

The browser then displays the specified user interface (i.e. selection list box) (step 703), from which 15 the user may select an alternative format (step 704). The selected alternative format then replaces the primary format in the display area of the browser (step 705). This step involves executing the Javascript associated with the list box element selected by the user.

20 Referring now to **Figure 8**, a pictorial diagram illustrating ALT menu on a web page is depicted in accordance with the present invention. The web page 800 has two multimedia resources: a video clip 801 and an image 802. In the present invention, after a web page is 25 displayed, the user right clicks on an image he wants to view in an alternate format. The browser looks through the DOM of the page, picks up the Javascript associated

30 with the image and pops up the corresponding XUL list box. The user then clicks on an element within the list box, which triggers (again by referring back to the DOM) another event associated with the item and replaces the

original image with the format chosen by the user.

In the first instance, in default browser settings, the video clip format **801** is shown. If the user right clicks, for example, on video clip **801** a pop up menu **811** appears containing alternate formats such as audio, jpeg, and text. The user may then select an alternate format from menu **811**, which will replace the default video clip **801** in the display.

The other multimedia resource on web page **800** is an image **802**. Like video clip **801**, image **802** is the primary format selected by the default browser setting. Again, if the user right clicks on image **802** a pop up menu **812** appears containing the alternate formats including text description, tactile transcoded depth map, and audio transcoded intensity map, which can be selected by the user to replace the default image **802**.

It should be pointed out that the alternate formats depicted in **Figure 8** are merely examples, as is the use of right clicking with a mouse to view the ALT menu. Numerous alternate formats exist for multimedia resources on web pages, and are well known within the art, as are various methods for accessing pop up menus. In addition, the menu of alternate formats can be presented by non visual means, such as an audio or tactile menu.

The present invention allows users to choose the way they want to access multimedia resources on a per-resource basis, depending on the options available.

Users can also choose to access a given resource in multiple formats. The present invention is also useful to users without impairments because the ALT tag information is no longer buried in the HTML code. Users

can easily access the tag information to actively choose in which format they wish to access web page contents.

It is important to note that while the present invention has been described in the context of a fully functioning data processing system, those of ordinary skill in the art will appreciate that the processes of the present invention are capable of being distributed in the form of a computer readable medium of instructions and a variety of forms and that the present invention applies equally regardless of the particular type of signal bearing media actually used to carry out the distribution. Examples of computer readable media include recordable-type media, such as a floppy disk, a hard disk drive, a RAM, CD-ROMs, DVD-ROMs, and transmission-type media, such as digital and analog communications links, wired or wireless communications links using transmission forms, such as, for example, radio frequency and light wave transmissions. The computer readable media may take the form of coded formats that are decoded for actual use in a particular data processing system.

The description of the present invention has been presented for purposes of illustration and description, and is not intended to be exhaustive or limited to the invention in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. The embodiment was chosen and described in

order to best explain the principles of the invention,
the practical application, and to enable others of
ordinary skill in the art to understand the invention for
various embodiments with various modifications as are
5 suited to the particular use contemplated.